



Luxury Vinyl Plank

1.5 mm & 2.0 mm

A revolutionary alternate to wooden floors that will last you a lifetime.

#Designed To Excel

All the images are from actual photoshoot. Color may vary depending upon your screen resolution.



PF-102

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-104

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-106

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-107

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-108

Size : 6" x 36" x 1.5 mm
24 pcs / Carton (3.34 Sqmtr)



PF-109

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-110

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-111

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-201

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-202

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-203

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-204

Size : 6" x 36" x 1.5 mm

24 pcs / Carton (3.34 Sqmtr)



PF-113

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-114

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-119

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-120

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-301

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-302

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)



PF-303


Size : 6" x 36" x 2.0 mm


24 pcs / Carton (3.34 Sqmtr)



PF-304

Size : 6" x 36" x 2.0 mm
24 pcs / Carton (3.34 Sqmtr)

DESCRIPTION			
Total Thickness	EN428	mm	1.5mm
Thickness of Wear layer	EN429	mm	0.1
Weight	EN430	g/m ²	2741
Plank Size	EN427	inch	6x36
Number of floor per package	-	-	24 PCS
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bf-1
Static electrical propensity	EN 1815	kv	< 2.0
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10
PERFORMANCE			
Wear resistance	EN 660.2	mm ³	≤2.0
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤0.15
Residual indentation	EN 433	mm	0.10
Thermal conductivity	EN 12524	W/(m.K)	0.21
Sound Reduction	DIN 52210	db	4.00
Color fastness	EN 20 105 - B02	degree	≥6
Chemical products resistance	EN 423	-	Pass
Surface treatment	-	-	UV
CE MARKING			
	EN 14041 : 2004		

DESCRIPTION			
Total Thickness	EN428	mm	2.0mm
Thickness of Wear layer	EN429	mm	0.2
Weight	EN430	g/m ²	3659
Plank Size	EN427	inch	6x36
Number of floor per package	-	-	24 PCS
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bf-1
Static electrical propensity	EN 1815	kv	< 2.0
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10
PERFORMANCE			
Wear resistance	EN 660.2	mm ³	≤2.0
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤0.15
Residual indentation	EN 433	mm	0.10
Thermal conductivity	EN 12524	W/(m.K)	0.21
Sound Reduction	DIN 52210	db	4.00
Color fastness	EN 20 105 - B02	degree	≥6
Chemical products resistance	EN 423	-	Pass
Surface treatment	-	-	UV
CE MARKING			
	EN 14041 : 2004		



www.excelwallpapers.com