


EXCEL

# Prime Floors

Luxury Vinyl Plank





DESCRIPTION			
Total Thickness	EN428	mm	1.5mm
Thickness of Wear layer	EN429	mm	0.1
Weight	EN430	g/m <sup>2</sup>	2741
Plank Size	EN427	inch	6x36
Number of floor per package	-	-	24 PCS
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bf-1
Static electrical propensity	EN 1815	kv	< 2.0
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10
PERFORMANCE			
Wear resistance	EN 660.2	mm <sup>3</sup>	≤2.0
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤0.15
Residual indentation	EN 433	mm	0.10
Thermal conductivity	EN 12524	W/(m.K)	0.21
Sound Reduction	DIN 52210	db	4.00
Color fastness	EN 20 105 - B02	degree	≥6
Chemical products resistance	EN 423	-	Pass
Surface treatment	-	-	UV
CE MARKING			
		EN 14041 : 2004	

# Prime Floors

Luxury Vinyl Plank







PF-102



PF-107



PF-110



PF-111



PF-204

**NEW**



PF-108



# Prime Floors

24 pcs / Carton  
(3.34 Sqmtr)


Size : 6" x 36" x 1.5 mm  
Wear Layer : 0.1 mm  
(152.4 mm x 914.4 mm x 1.5 mm)



PF-104



PF-106



PF-109



PF-201 **NEW**



PF-202 **NEW**



PF-203 **NEW**



# Prime Floors

24 pcs / Carton  
(3.34 Sqmtr)

Size : 6" x 36" x 2.0 mm  
Wear Layer : 0.2 mm  
(152.4 mm x 914.4 mm x 2.0 mm)



PF-301

**NEW**



PF-302

**NEW**



PF-303

**NEW**



PF-304

**NEW**



**Prime Floors**

24 pcs / Carton  
(3.34 Sqmtr)

Size : 6" x 36" x 2.0 mm  
Wear Layer : 0.2 mm  
(152.4 mm x 914.4 mm x 2.0 mm)



**PF-113**



**PF-114**




**PF-119**



**PF-120**



DESCRIPTION			
Total Thickness	EN428	mm	2.0mm
Thickness of Wear layer	EN429	mm	0.2
Weight	EN430	g/m <sup>2</sup>	3659
Plank Size	EN427	inch	6x36
Number of floor per package	-	-	24 PCS
CLASSIFICATION			
Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13 501-1	class	Bf-1
Static electrical propensity	EN 1815	kv	< 2.0
Slip resistance wet: ramp test with oil	DIN 51 130	class	R10
PERFORMANCE			
Wear resistance	EN 660.2	mm <sup>3</sup>	≤2.0
Wear group	EN 649	-	T
Dimensional stability	EN 434	%	≤0.15
Residual indentation	EN 433	mm	0.10
Thermal conductivity	EN 12524	W/(m.K)	0.21
Sound Reduction	DIN 52210	db	4.00
Color fastness	EN 20 105 - B02	degree	≥6
Chemical products resistance	EN 423	-	Pass
Surface treatment	-	-	UV
CE MARKING			
		EN 14041 : 2004	

# Prime Floors

Luxury Vinyl Plank

