



Prime Floors

*Impressive
luxury*

SPC FLOORING 4mm

Instant makeover with out any Dust & Noise

#Designed To Excel

All the images are from actual photoshoot. Color may vary depending upon your screen resolution.



EX2001

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2002

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2003

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2004

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2005

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2006

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2007

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2008

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2009

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2010

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2011

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)



EX2012

Size : 7.25" x 48" x 4 mm

10 pcs / Box (24.16 Sqft Approx)

ITEM		UNIT	TEST METHODS	SPEC	PRIME FLOOR SPC
Thickness		mm	ASTM F 386	±0.005"(0.13mm)	±0.005"(0.13mm)
Size	Width	mm	ASTM F 2055	184.15 ± 0.23	184.15 ± 0.23
	Length	mm		1220 ± 1.58	1220 ± 1.58
Squareness		mm	ASTM F 2055	Max. 0.01"(0.254mm)	≤ 0.2
Gloss level		-	60° Gloss Meter		5 - 8
Size	Width	%	ASTM F 2199-09	≤ 0.002"(0.165%)	≤ 0.1%
	Length	%		≤ 0.002"(0.165%)	≤ 0.1%
Size	23°C	mm			≤ 0.5mm
	-10°C x 2hr	mm			≤ 0.5mm
Core Density		-			1.95 ± 0.05
Contraction (-10°C, 2hr)	Width	%	-10°C x 2hr		≤ 0.2%
	Length	%			≤ 0.2%
Expansion (50°C, 4hr)	Width	%	50°C x 4hr		≤ 0.2%
	Length	%			≤ 0.2%
Indentation		%	ASTM F 1914	≤ 8%	≤ 5%
Resistance to Chemicals			ASTM F 925 (Resistance to Chemicals)	No more than slight change in surface dulling, surface attack, or staining	No more than slight change in surface dulling, surface attack, or staining
IIC			ASTM F 492-09	≥ 50	≥52
Static Load Limit			ASTM F 970	0.005"(0.13mm)	0.005"(0.13mm)
Pieces/Box				10 pcs	10 pcs
Sq.Mt./Box				2.25	2.25
CLICK				UNICLIC	UNICLIC



Lower Thickness
& Weight



Extra Wide
Planks



Impact
Resistances



Easy to
Clean Floor



Green
Product



Dust free



Flame
Resistant



Scratch
Resistant



Termite
Resistant



Water Proof



Recyclable




Weather
Proof



Stain
Free



Easy to
Carry



Quick
Installation



Glue
Free



www.excelwallpapers.com